

**SERVING AND CLEAN-UP TROLLEYS**

from BLANCO:

Unsurpassed quality and stability.

blanco  
servingtrolley

## The BLANCO stability package: A first-class finish for a long service life.

In the catering industry, there is often a lot of running back and forth. To prevent things from getting mixed up, we recommend the **servicing and clean-up trolleys from BLANCO**. They have a high-quality finish and, with a maximum **stability and carrying capacity**, also guarantee the maneuverability required during peak periods.

The serving and clean-up trolleys are available in all sizes, as well as with 2, 3, 4 or 5 shelves for large capacities. Whether it's transport, temporary or long-term storage – BLANCO offers the ideal model for **any requirements**.



## Short-term delivery, long-term use. Serving and clean-up trolleys from BLANCO.

The BLANCO serving and clean-up trolleys are manufactured from high-quality stainless steel and are a lifetime investment. Excellent materials and high production standards ensure quality that sets standards.

Thanks to the large deep-drawn profile edge, you can be sure that nothing slips over the shelf's rim. Many convenient details, various castor designs com-

binated with practical accessories round off this top product line.

By the way: Although otherwise it's only possible to order large quantities and long waiting times are to be expected, outstanding service awaits you at BLANCO.

The most popular models from the BLANCO range of serving and cleaning-

up trolleys are readily **available from stock** and therefore are obtainable for use in a short span of time.

**Typically BLANCO: More quality. More service. More options.**



### Integrated noise dampers

Quiet! A noise-insulation mat is mounted on the underside of each shelf and this greatly reduces that annoying rolling noise.



### Curled edges

The curled edges and the large deep-drawn profile edge make the shelf stable and ensure an extremely high load-bearing capacity. In addition, they also protect the personnel from injuries.



### Shelves with a profile edge

All shelves are produced with an all-round raised profile edge. This prevents anything from slipping over the edge – even when the going gets rough.



### More stability

A first-rate finishing! One-piece welded seams connect the tube frame to the shelves thus increasing the stability of the trolley.



### Impact protection is standard

All serving and clearing trolleys are equipped with a strong bumper rail in a new rugged design. They protect the trolley and inventory against damage.



### Even more stability

Gusset plates and reinforcing profiles are available on request. They increase the stability of the serving and clean-up trolleys – ideal under extreme loads.

## BLANCO SERVING TROLLEYS

SW 6x4 and SW 8x5



Model	<b>SW 6x4-2 Serving trolley</b>	<b>SW 6x4-3 Serving trolley</b>
Dimensions (L x W x H)	700 x 500 x 950 mm	700 x 500 x 950 mm
Spacing between shelves	585 mm	275 mm
Weight (synthetic castors)	11 kg	13 kg
Load-bearing capacity	120 kg	120 kg
Number of shelves	2 shelves	3 shelves
Shelf dimensions (L x W)	600 x 400 mm	600 x 400 mm
Max. load per shelf	80 kg	80 kg
Castor model	125 mm dia., 4 steering castors, 2 of which have locking brakes	
Castor variant Order No.	Synthetic* <b>569 767</b>	Synthetic* <b>569 768</b>
Castor variant Order No.	galvanized steel <b>566 246</b>	galvanized steel <b>566 247</b>

We will be happy to provide you with additional information on these products and the entire BLANCO product line on request (see back for address).

\*corrosion-resistant pursuant to DIN 18867-8



Model	<b>SW 8x5-2 Serving trolley</b>	<b>SW 8x5-3 Serving trolley</b>	<b>SW 8x5-4 Serving trolley</b>	<b>SW 8x5-5 Serving trolley</b>
Dimensions (L x W x H)	900 x 600 x 950 mm	900 x 600 x 950 mm	900 x 600 x 1290 mm	900 x 600 x 1290 mm
Spacing between shelves	585 mm	275 mm	285 mm	205 mm
Weight (synthetic castors)	15 kg	18 kg	21 kg	25 kg
Load-bearing capacity	120 kg	120 kg	120 kg	120 kg
Number of shelves	2 shelves	3 shelves	4 shelves	5 shelves
Shelf dimensions (L x W)	800 x 500 mm	800 x 500 mm	800 x 500 mm	800 x 500 mm
Max. load per shelf	80 kg	80 kg	80 kg	80 kg
Castor model	125 mm diameter, 4 steering castors, 2 of which have locking brakes			
Castor variant Order No.	Synthetic* <b>569 769</b>	Synthetic* <b>569 770</b>	Synthetic* <b>569 771</b>	Synthetic* <b>569 772</b>
Castor variant Order No.	galvanized steel <b>555 527</b>	galvanized steel <b>555 528</b>	galvanized steel <b>563 437</b>	galvanized steel <b>563 438</b>

\*corrosion-resistant pursuant to DIN 18867-8

# BLANCO SERVING TROLLEYS

## SW 9x6 and SW 10x6



Model	SW 9x6-2 Serving trolley	SW 9x6-3 Serving trolley	SW 9x6-4 Serving trolley	SW 9x6-5 Serving trolley
Dimensions (L x W x H)	1000 x 650 x 950 mm	1000 x 650 x 950 mm	1000 x 650 x 1290mm	1000 x 650 x 1290mm
Spacing between shelves	585 mm	275 mm	285 mm	205 mm
Weight (synthetic castors)	18 kg	20 kg	30 kg	29 kg
Load-bearing capacity	120 kg	120 kg	120 kg	120 kg
Number of shelves	2 shelves	3 shelves	4 shelves	5 shelves
Shelf dimensions (L x W)	900 x 550 mm	900 x 550 mm	900 x 550 mm	900 x 550 mm
Max. load per shelf	80 kg	80 kg	80 kg	80 kg
Castor model	125 mm diameter, 4 steering castors, 2 of which have locking brakes			
Castor variant Order No.	Synthetic* <b>569 773</b>	Synthetic* <b>569 774</b>	Synthetic* <b>569 775</b>	Synthetic* <b>569 776</b>
Castor variant Order No.	galvanized steel <b>555 531</b>	galvanized steel <b>555 532</b>	galvanized steel <b>563 448</b>	galvanized steel <b>563 449</b>

\*corrosion-resistant pursuant to DIN 18867-8



Model	SW 10x6-2 Serving trolley	SW 10x6-3 Serving trolley	SW 10x6-4 Serving trolley	SW 10x6-5 Serving trolley
Dimensions (L x W x H)	1100 x 700 x 1000 mm	1100 x 700 x 1000 mm	1100 x 700 x 1350 mm	1100 x 700 x 1350 mm
Spacing between shelves	585 mm	275 mm	285 mm	205 mm
Weight (synthetic castors)	23 kg	28 kg	40 kg	42 kg
Load-bearing capacity	160 kg	200 kg	200 kg	200 kg
Number of shelves	2 shelves	3 shelves	4 shelves	5 shelves
Shelf dimensions (L x W)	1000 x 600 mm	1000 x 600 mm	1000 x 600 mm	1000 x 600 mm
Max. load per shelf	80 kg	80 kg	80 kg	80 kg
Castor model	125 mm diameter, 4 steering castors, 2 of which have locking brakes			
Castor variant Order No.	Synthetic* <b>569 778</b>	Synthetic* <b>569 780</b>	Synthetic* <b>569 782</b>	Synthetic* <b>569 784</b>
Castor variant Order No.	galvanized steel <b>555 536</b>	galvanized steel <b>555 538</b>	galvanized steel <b>563 459</b>	galvanized steel <b>563 462</b>
Castor model	125 mm diameter, 2 fixed castors, 2 steering castors with locking brakes			
Castor variant Order No.	Synthetic* <b>569 777</b>	Synthetic* <b>569 779</b>	Synthetic* <b>569 781</b>	Synthetic* <b>569 783</b>
Castor variant Order No.	galvanized steel <b>555 535</b>	galvanized steel <b>555 537</b>	galvanized steel <b>563 458</b>	galvanized steel <b>563 461</b>

\*corrosion-resistant pursuant to DIN 18867-8

## BLANCO SERVING AND CLEARING TROLLEYS

### SW 10 x 6 BASIC and ARW



Model	SW 10 x 6-2 BASIC Serving trolley	SW 10 x 6-3 BASIC Serving trolley	SW 10 x 6-4 BASIC Serving trolley	SW 10 x 6-5 BASIC Serving trolley
Dimensions (L x W x H)	1100 x 700 x 950 mm	1000 x 700 x 950 mm	1100 x 700 x 1290 mm	1100 x 700 x 1290 mm
Spacing between shelves	585 mm	275 mm	285 mm	205 mm
Weight (synthetic castors)	20 kg	23 kg	34 kg	37 kg
Load-bearing capacity	120 kg	120 kg	120 kg	120 kg
Number of shelves	2 shelves	3 shelves	4 shelves	5 shelves
Shelf dimensions (L x W)	1000 x 600 mm	1000 x 600 mm	1000 x 600 mm	1000 x 600 mm
Max. load per shelf	80 kg	80 kg	80 kg	80 kg
Castor model	125 mm diameter, 4 steering castors, 2 of which have locking brakes			
Castor variant Order No.	Synthetic* <b>573 486</b>	Synthetic* <b>573 488</b>	Synthetic* <b>573 490</b>	Synthetic* <b>573 492</b>
Castor variant Order No.	galvanized steel <b>573 487</b>	galvanized steel <b>573 489</b>	galvanized steel <b>573 491</b>	galvanized steel <b>573 493</b>





\*corrosion-resistant pursuant to DIN 18867-8



Model	ARW 9 x 6-2 Clearing trolleys	ARW 9 x 6-3 Clearing trolleys	ARW 10 x 6-2 Clearing trolleys
Dimensions (LxWxH)	1000 x 650 x 1030 mm	1000 x 650 x 1030 mm	1100 x 700 x 1010 mm
Spacing between shelves	585 mm	275 mm	481 mm
Weight (synthetic castors)	19 kg	23 kg	25 kg
Load-bearing capacity	120 kg	120 kg	160 kg
Number of shelves	2 shelves	3 shelves	2 shelves
Shelf dimensions (LxW)	900 x 550 mm	900 x 550 mm	1000 x 600 mm
Max. load per shelf	80 kg	80 kg	80 kg
Castor model	125 mm diameter, 4 steering castors, 2 of which have locking brakes		
Castor variant Order No.	Synthetic* <b>569 786</b>	Synthetic* <b>569 787</b>	Synthetic* <b>569 788</b>
Castor variant Order No.	galvanized steel <b>563 022</b>	galvanized steel <b>563 055</b>	galvanized steel <b>563 095</b>
Castor model	125 mm diameter, 2 fixed castors, 2 steering castors with locking brakes		
Castor variant Order No.	--	--	Synthetic* <b>569 789</b>
Castor variant Order No.	--	--	galvanized steel <b>563 090</b>

\*corrosion-resistant pursuant to DIN 18867-8

## Accessories for Serving and Clearing trolleys

Illustration	Model	Designation	Dimensions Capacity	Order No.
	AFB 4 x 2 x 2,5	<b>Garbage container</b> of stainless steel, deep-drawn, with hanging device, can be mounted on and removed from push handle (not suitable for SW 6x4)	425 x 225 x 250 mm 18.5 liters	555 509
	BGN 1/3-150	<b>Cutlery container</b> of stainless steel, deep-drawn, with hanging device, can be mounted on and removed from push handle	325 x 176 x 150 mm 110 pieces of cutlery	555 510
	Railing	<b>Railing.</b> all-round, 50 mm high, for all SW models	--	Please specify when ordering
	Gusset plates	<b>Gusset plates</b> 4 per shelf, except on bottom shelf, for all SW models	--	Please specify when ordering
not shown	Reinforcing profile	<b>Shelf reinforcing profile per shelf</b> for the models: SW 8x5, SW 9x6, SW 10x6	--	Please specify when ordering
	Air-identical castors	<b>Air-identical castors</b> , 125 mm dia., 4 steering castors, 2 of which have brakes, for the models: SW 6x4, SW 8x5, SW 9x6, SW 10x6 BASIC, ARW 9x6	--	Please specify when ordering
	Pneumatic-tired castors	<b>Pneumatic-tired castors</b> , 180 mm dia., 4 steering castors, for the models: SW 6x4, SW 8x5, SW 9x6, SW 10x6 BASIC, ARW 9x6	--	Please specify when ordering



We will be happy to provide you with additional information on these products and the entire BLANCO product line on request (see back for address).

**BLANCO SW 8x5-3**  
Serving trolley with synthetic castors



**BLANCO**  
PROFESSIONAL

125424, г. Москва, Волоколамское шоссе, д. 88, стр. 8

Тел./факс: +74955404600

**РУССКИЙ ПРОЕКТ**<sup>®</sup>  
[www.rp.ru](http://www.rp.ru)